

Product Name *Water Repellent Oil*

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	<i>Water Repellent Oil</i>
Recommended use:	Penetrant
Company Details:	Envirochem International (NZ) Ltd
Address:	59C Allens Road, East Tamaki Auckland. New Zealand
Telephone Number:	+64 9 262 0800
Emergency Telephone Number:	National Poison Information Centre 0800 764 766
Date of Preparation:	01/04/2022

2. HAZARD IDENTIFICATION



HSNO Hazard Classification: 3.1D, 6.1E, 6.3B, 6.7B, 9.1B

Hazard Statement:

Combustible Liquid.
May be harmful if swallowed.
Cause mild skin irritation.
Suspected of causing cancer.
Toxic to aquatic life with long lasting effects

Prevention Statements:

- Keep out of reach of children.
- Read label before use.
- Read Safety Data Sheet before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. -No smoking.
- Avoid release into environment
- Use personal protective equipment as required

Response Statement:

- If medical advice is needed, have product container or label at hand.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- Do NOT induce vomiting.
- Collect spillage.
- If skin irritation occurs: Get medical advice/ attention.
- In case of fire: Use foam or water mist (Small fires: carbon dioxide, dry chemical, sand) for extinction

Storage Statement:

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Disposal

- Disposal should be through qualified contractor.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS #	Concentration %
Hydrocarbon solvents		>75
Products not considered Hazardous		Balance

4. FIRST AID MEASURES

Ingestion:

Immediately rinse mouth with water. If swallowed do not induce vomiting. Give water to drink. Never give anything by mouth to an unconscious person. Seek immediate medical aid immediately.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment. Do not rub eyes or keep eyes closed

Skin Contact:

Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.

Inhalation:

Remove the effected person out to a ventilated area. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

5. FIRE FIGHTING MEASURE

Extinguishing Media:

Use dry chemical powder, foam, polymer foam, and water spray or fog type extinguishers. Water may be ineffective on fire. However, water spray may be used to extinguish fires and to absorb heat. Keep containers cool and protect exposed material. If a leak or spill has not ignited, water spray may be used to flush spills away from exposures.

Unsuitable Extinguishing Media

Do not use a water jet

Hazards from combustion products:

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising from The Chemical

Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Decomposition Temperature

Not Available

Precautions in Connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Precautions:

Personnel involved in the clean up should wear full protective clothing. Extinguish or remove all sources of ignition. Evacuate all unnecessary personnel. Increase ventilation. Avoid walking through spilled product as it may slippery. Stop leak if safe to do so. Do not let product reach drain or waterways; advise the Environmental Protection Authority or your local Waste Management. Use clean, non-sparking tools and equipment.

Methods and Materials for Containment and Clean Up:

Soak up spilled product using inert absorbent, non-combustible material such as sand or soil. Avoid using sawdust or cellulose. When saturated, collect material into suitable, labelled, dry, sealable containers and hold for safe disposal. Use clean non-sparking tools to collect the material and place in labelled containers. Once pick-up is complete, flush spill site with plenty of water to eliminate any residue. Hold contaminated water for treatment/disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measure against static discharges. Earth or bon all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using toilet facilities. Avoid exposure. Do not handle until safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated area away from sources of ignition, Oxidising agents, strong acids, foodstuffs and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity charges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 – The storage and handling of flammable and combustible liquids. References should also be made to all applicable local and national regulations.

Recommended Materials

For containers, or container lining use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards:

The Occupational Safety and Health Service, NZ Department of Labour have set no Tolerable Exposure Limit (TEL) Workplace Exposure Standards (WES) for this substance.

Biological Limit Values:

Data not available

Other Exposure Information

Oil Mist, mineral
TWA: 5 mg/m³
STEL: 10 mg/m³

Engineering Controls:

The use of local exhaust ventilation (Flame Proof) is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment

PERSONAL PROTECTIVE EQUIPMENT:

Respiratory Protection:

Where concentration in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

Eye Protection:

Always use safety glasses or a face shield when handling this product.

Skin/Body Protection:

Always wear long sleeves and long trousers or coveralls, enclosed footwear or safety boots and chemical resistant gloves when manufacturing this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Pale Brown
Physical State:	Liquid
Odour:	Characteristic oil Odour
Decomposition temperature	Not Available
Melting Point:	Not Available
pH:	Not Applicable
Solubility:	Negligible
Density:	830 kg/m ³ @ 15 deg
Boiling point:	180 Deg
Ignition Point:	350 deg (ASTM E-659)
Flash Point:	80 Deg (Closed Cup)
Vapour pressure:	<0.54 mmHg @ 25 deg
Flammable Limits – Lower	1.0% v/v
Flammable Limits – Upper	6% v/v
Kinematic Viscosity	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable under normal condition of storage and handling

Conditions to avoid:

Avoid heat, open flame and other sources of ignition.

Incompatible Materials:

Incompatible with strong Oxidising agents

Hazardous decomposition:

Thermal decomposition may result in the release of toxic and/or irritating fumes including: organic compounds, carbon dioxide and carbon monoxide.

Hazardous reactions:

Reacts with incompatible materials.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with the safety data sheet. Symptoms or effects that may arise if the product is mishandled and the overexposure occurs are: **Acute Effects**

Effects

Ingestion:

Small amounts of liquid aspirated into lungs during ingestion, or from vomiting. Ingestion of large amounts of this product will result in headaches, nausea, dizziness and tracheal burning.

Eye Contact:

May cause eye irritation. On eye contact this product will cause tearing, stinging, blurred vision and redness.

Skin Contact:

This product is irritating to skin. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis

Inhalation:

Irritating to respiratory tract. Exposure to high concentrations over an extended period of time may result in muscle weakness, tingling in hands and feet, blurred vision, headaches, nausea, loss of appetite, hallucinations and possible loss of consciousness.

Toxicological information

Actual oral toxicity	LD50 (rat): >5000mg/kg
Acute dermal toxicity	LD50 (rat): >2000mg/kg
Acute Inhalation toxicity	LC50: >5mg/l

Information given is based on product, and/or similar products, and/or components.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects. Available toxicity data is given below. The data are derived from the evaluations or test results achieved with similar products (conclusion by analogy).

Persistence/ degradability:

Inherently biodegradable. Oxidises rapidly by photo-chemical reactions in air.

Mobility:

Floats on water. Absorbs to soil and is not mobile

Bio accumulative Potential:

Expected to be bio accumulative

Other Adverse Effects

In view from the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature.

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful.

Special precautions for landfill or incineration:

This product is not suitable for disposal by either landfill or via municipal sewers, drain, natural streams or rivers. This product is ash less and can be burned directly in appropriate equipment.

14. TRANSPORT INFORMATION

Road and Rail Transport:

Classified as Dangerous Goods by the criteria of New Zealand Dangerous Goods Code for transport by road and rail

Marine Transport:

Classified as Dangerous Goods by the criteria of international Maritime Dangerous Goods Code for transport by sea.

Air Transport:

Classified as Dangerous Goods by the criteria of international Air Association Dangerous Goods Regulations for transport by air



Shipping Name:	Flammable Liquid N.O.S
Hazard Class:	3
UN Number:	UN 1993
Packing Group:	III
Hazchem Code:	3YE

15. REGULATORY INFORMATION

HSNO Approval No:	HSR001441
Group Standard:	Petrol and Petroleum Products Group Standard 2006
HSNO Classification:	3.1D, 6.1E, 6.3B, 6.7B, 9.1B

16. OTHER INFORMATION

New Zealand National Poison Information Centre:	0800 764 766
New Zealand Emergency Services:	111
Envirochem International (NZ) Ltd :	+64 9 262 0800

Every endeavour has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. Envirochem International (NZ) Limited accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product is in compliance with appropriate Local Councils regulations.